

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
29 March 2001 (29.03.2001)


PCT

(10) International Publication Number  
WO 01/22522 A1

- (51) International Patent Classification<sup>7</sup>: H01M 12/06 (72) Inventors; and  
(75) Inventors/Applicants (for US only): MOLLOY, Kevin [US/US]; 14 Oakdale Road, Canton, MA 02021 (US). THOMPSON, John [US/US]; 81 Pine Street, Medfield, MA (US). YONJAN, Bikram [NP/US]; 52 Prospect Street, Unit 2, Watertown, MA 02472 (US). YOPPOLO, Robert [US/US]; 6 Fair Oaks Circle, New Milford, CT 06776 (US).
- (21) International Application Number: PCT/US00/25686
- (22) International Filing Date:  
20 September 2000 (20.09.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (74) Agents: HANDELMAN, Joseph, H.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 et al. (US).
- (30) Priority Data:  
09/400,020 21 September 1999 (21.09.1999) US
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:  
US 09/400,020 (CON)  
Filed on 21 September 1999 (21.09.1999)
- (71) Applicant (for all designated States except US): THE GILLETTE COMPANY [US/US]; Prudential Tower Building, Boston, MA 02199 (US).
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: AIR MANAGER SYSTEM FOR METAL AIR BATTERY



(57) Abstract: An air manager system for a metal air cell is disclosed. The system includes: (a) a housing (2, 4) having an air mover (30) and an air outlet opening; and (b) a cartridge that is removable from the housing. The cartridge includes (i) a metal air cell (6); (ii) an air inlet opening (46) located toward a first end of the cartridge and adjacent to a first side of the cartridge; (iii) an air outlet opening (48) located toward a second end of the cartridge and adjacent to a second side of the cartridge; (iv) a first diffusion tube (26) communicating with the air inlet opening (25) of the cartridge distributor; (v) a second diffusion tube communicating with the air outlet opening of the cartridge; (vi) a first tube (28) communicating with the first diffusion tube (26), and (vii) a second distributor tube communicating with the second diffusion tube.

WO 01/22522 A1



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

**Published:**

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

AIR MANAGER SYSTEM FOR METAL AIR BATTERY

The invention generally relates to an air manager system for a metal air battery.

Batteries are commonly used electrical energy sources. A battery  
5 contains a negative electrode, typically called the anode, and a positive electrode,  
typically called the cathode. The anode contains an active material that can be  
oxidized; the cathode contains or consumes an active material that can be reduced.  
The anode active material is capable of reducing the cathode active material. In  
order to prevent direct reaction of the anode material and the cathode material, the  
10 anode and the cathode are electrically isolated from each other by a sheet-like layer,  
typically called the separator.

When a battery is used as an electrical energy source in a device,  
such as a cellular telephone, electrical contact is made to the anode and the cathode,  
allowing electrons to flow through the device and permitting the respective  
15 oxidation and reduction reactions to occur to provide electrical power. An  
electrolyte in contact with the anode and the cathode contains ions that flow through  
the separator between the electrodes to maintain charge balance throughout the  
battery during discharge.

In a metal air electrochemical cell, oxygen is reduced at the cathode,  
20 and a metal is oxidized at the anode. Oxygen is supplied to the cathode from the  
atmospheric air external to the cell through one or several air access port(s) in the  
container.

During periods of inactivity, there is no need for air from the  
environment to diffuse into the cell. In fact, it is preferred that the supply of air to  
25 the cell be minimized, because the diffusion of air into the cell can lead to changes  
in the humidity level of the cell. When the humidity level of the outside  
atmosphere is lower than that of the cell, the cell can dry out. When the humidity  
level of the outside atmosphere is higher than that of the cell, the cell can flood. In  
addition, when air diffuses into the cell, the anode can become prematurely  
30 oxidized.

An air manager system enhances the activated storage life of a  
metal-air battery system by controlling the flow of air, which includes oxygen,

carbon dioxide, and water, into and out of the system. During periods of battery use, an air mover, such as a fan, moves enough air into and out of the system to ensure good performance.

5 The distribution of air flow across the active surfaces of the cells can be uneven. Uneven air flow can result in "hot spots" in the battery, where the anode and the cathode react more than in other areas of the battery. Hot spots can lead to inconsistent battery performance and failure to realize the maximum capacity of the battery.

10 The air manager system of the invention provides for improved activated storage life of the battery contained in the system and provides for good performance of the battery during use. Air is directed across active surfaces of the battery evenly, thus optimizing performance. In addition, the system is designed for ease of use by the consumer.

15 In one aspect, the invention features an air manager system for a metal air cell. The system includes: (a) a housing having an air mover and an air outlet opening; and (b) a cartridge that is removable from the housing. The cartridge includes (i) a metal air cell; (ii) an air inlet opening located toward a first end of the cartridge and adjacent to a first side of the cartridge; (iii) an air outlet opening located toward a second end of the cartridge and adjacent to a second  
20 side of the cartridge; (iv) a first diffusion tube communicating with the air inlet opening of the cartridge, the first diffusion tube extending along the first side of the cartridge; (v) a second diffusion tube communicating with the air outlet opening of the cartridge, the second diffusion tube extending along the second side of the cartridge; (vi) a first distributor tube communicating with the first diffusion tube,  
25 the first distributor tube extending from the first diffusion tube along the first side of the cartridge through a change of direction and being adjacent to an air plenum, the first distributor tube including a plurality of openings communicating with the air plenum; and (vii) a second distributor tube communicating with the second diffusion tube, the second distributor tube extending from the second diffusion tube  
30 along the second side of the cartridge through a change of direction and being adjacent to the air plenum, the second distributor tube including a plurality of openings communicating with the air plenum.

The air mover can move air into the air inlet opening of the cartridge and/or extract air from the air outlet opening of the cartridge. The diffusion tube or tubes help to minimize the transport of water vapor into and out of the cartridge during periods of inactivity. The diffusion tubes therefore help to prevent the cells  
5 from flooding or drying out.

When the metal air cell has been depleted, the cartridge can be removed from the housing and replaced with a fresh cartridge. The housing, including the air mover, can be re-used with the new cartridge, instead of being replaced. This design helps to minimize the cost of using the air manager system.  
10 It also reduces the size of the cartridge, which in turn minimizes the amount of waste generated when the cartridge must be replaced.

In another aspect, the invention features an air manager system for a metal air cell. The system includes: (a) a housing having an air mover and an air outlet opening; and (b) a cartridge that is removable from the housing. The  
15 cartridge includes (i) a metal air cell; (ii) an air inlet opening; (iii) an air outlet opening; (iv) a first diffusion tube in communication with the air inlet opening and a second diffusion tube in communication with the air outlet opening; (v) a first distributor tube in communication with the first diffusion tube and a second distributor tube in communication with the second diffusion tube; and (vi) a first  
20 panel defining a plurality of openings communicating with the first distributor tube and a second panel defining a plurality of openings communicating with the second distributor tube. The diffusion tubes, the distributor tubes, and the openings cooperate to define a plurality of air flow paths that start at the air inlet opening of the cartridge, continue through the cartridge, and end at the air outlet opening of the  
25 cartridge. All of these air flow paths are substantially equal in length.

In another aspect, the invention features a method for controlling air flow in a metal air battery. The method includes: (a) confining at least one metal air cell within a cartridge having an air inlet opening and an air outlet opening; and (b) moving air through any of a plurality of air flow paths within the cartridge.  
30 Each of these air flow paths passes through the air inlet opening of the cartridge, through a diffusion tube, through a distributor tube, across an active surface of a cell, and through the air outlet opening of the cartridge. All of the air flow paths are

substantially equal in length. The method can include moving air into the air inlet opening of the cartridge and/or extracting air from the air outlet opening of the cartridge.

Air from the atmosphere is forced into the cartridge by air discharged  
5 from an air mover, such as a blower, or pulled out of the cartridge as intake air supplied to an air mover, such as a vacuum device. It flows across the active surface of the cell contained in the cartridge, then exits the cartridge, rather than being recycled through the cartridge.

As used herein, "removable" means that a component can be easily  
10 removed, for example, by a consumer, without the need for tools or excessive force.

As used herein, "toward" means at a position on a member, relative to a given point on that member, within 30%, more preferably 20% or 10%, of the total length of the member. A feature located toward an end of a bar having a length of 10 cm is within 3 cm of that end of the bar, and is preferably 2 cm or 1  
15 cm from the end.

Other features and advantages of the invention will be apparent from the description of the preferred embodiment thereof, and from the claims.

Fig. 1 is an exploded view of a cartridge of the invention.

Fig. 2 is a cutaway view of a cartridge of the invention.

20 Fig. 3 is a top cross sectional view of a cartridge of the invention.

Fig. 4 is an exploded view of an air manager system of the invention.

Fig. 5 is a pictorial view of an air manager system of the invention.

The air manager system of the invention can be used with devices such as cellular telephones. Air is directed across the active surfaces of the metal  
25 air cells uniformly, so relatively consistent battery performance can be achieved.

Referring to Fig. 1, a cartridge includes a lower casing 2 and an upper casing 4. The cartridge may be made of any material that is impermeable to air, such as plastic or metal, or a combination thereof. Four metal air cells 6 are contained within the cartridge. Any type of metal-air cell, for example, prismatic  
30 cells, button cells, cylindrical cells, and bipolar construction cells can be used. The cells can be prepared, for example, as described in Linden, Handbook of Batteries, 2d ed. (1995). The cells are arranged in stacks of two. The cells within each stack

are spaced apart vertically to define an air flow path 8 between the cells in the stack. The cathodes (the active surfaces) of these cells face each other within these stacks. The stacks are spaced apart horizontally.

An interior panel 10 of the cartridge has a plurality of openings 12.

- 5 In addition, panel 10 has a ridge 14. When assembled, panel 10, ridge 14, and cartridge wall 16 define a long, thin path that serves as a diffusion tube and as a distributor tube for the cartridge. The openings 12 communicate with the distributor tube.

- 10 Interior panel 20 also includes a ridge (not shown). Interior panel 20, the ridge, and cartridge wall 22 define an air exit plenum that includes a second distributor tube and a second diffusion tube. Interior panel 20 has openings 24 that communicate with the distributor tube. In this embodiment, the diffusion tubes and the distributor tubes are integrated into the cartridge and therefore cannot be removed from the cartridge. This design is space efficient, and cartridges with this
- 15 design are relatively inexpensive to produce.

- Referring to Fig. 2, air flows into the air inlet opening of the cartridge, as indicated by arrow 25. It flows along the length of the diffusion tube 26, then turns about 180°. It flows through distributor tube 28, turns about 90°, then flows through the openings 12. After the air flows across the cells, it is
- 20 collected in a second distributor tube (not shown). It turns about 180°, flows through a second diffusion tube (not shown), then exits the cartridge through the air outlet opening, as indicated by arrow 31.

- The diffusion tubes and distributor tubes are connected through approximately 180° turns. The turns make the air paths relatively convoluted, and
- 25 therefore help to increase the isolation of the cells when the fan is off.

- Referring to Fig. 3, the air flow paths through the cartridge are shown in more detail. Air enters the cartridge through air inlet opening 46. The air flows through a diffusion tube (not shown), through a distributor tube (not shown), and through openings 12. For clarity, not all of the openings are shown. The air
- 30 flows across the cells, then through openings 24. The air then flows through a second distributor tube (not shown), through a second diffusion tube, then through air outlet opening 48.

As shown in Fig. 3, air can take any of air flow paths a, b, or c when flowing through the cartridge. The lengths of these paths, from the air inlet opening of the cartridge, through the cartridge, to the air outlet opening of the cartridge, are substantially the same. Therefore, all portions of the active surfaces are exposed to substantially the same amount of air flow, and problems such as "hot spots" and cell imbalance can be avoided.

The configuration and the size of the diffusion tubes help to keep air flow through the cartridge to a minimum when the blower 30 is off. Each of the diffusion tubes has a cross-sectional area of about 1 mm<sup>2</sup> to about 8 mm<sup>2</sup> and a length of about 10 mm to about 70 mm. The diffusion tubes are sized to permit a flow rate through the cartridge of about less than about  $3.46 \times 10^{-2}$  L/hour, preferably less than about  $3.46 \times 10^{-3}$  L/hour, when the air mover is off. Limited air flow helps to minimize the self-discharge of the battery and to reduce carbonization of the electrolyte. It also helps to maintain a constant humidity level in the cell, and helps to minimize the amount of oxygen and CO<sub>2</sub> entering the cell. Although limited air flow has many advantages, it is preferred that at least some oxygen remains in the cell. If the level of oxygen is too low, it can be difficult for the air mover to switch on after a period of inactivity.

The metal air cells 6 in the cartridge cooperate to define a battery that delivers a current of at least 300 mA when the air mover is on. In some embodiments, the battery delivers a current of at least 500 mA, 900 mA, 1000 mA, or 1700 mA when the air mover is on. In other embodiments, the battery has an output current density of about 1 to about 200 mA/cm<sup>2</sup>, for example, about 10 to about 110 mA/cm<sup>2</sup>, of air cathode surface when the air mover is on.

Referring to Fig. 4, the housing includes a cover 32, a blower 30, an air outlet opening 33, a pack release button 34, a cartridge contact 38, and a base 42. The housing 44 for the blower is built into the pack housing, so there is no need for a separate case for the blower. The cartridge includes alignment tabs 45 that help the user position the cartridge in the proper orientation.

When the voltage drops below a certain level, the blower 30 turns on. When the blower is on, air is moved from the air outlet opening 33 of the housing to the air inlet opening 46 of the cartridge. Air moves through the cartridge as



described above, then exits the cartridge through the air outlet opening 48.

Referring to Fig. 5, the locking tab 50 of the cartridge and the cartridge release latch 52 of the housing interlock to hold the cartridge in the housing. The cartridge release latch also serves the purpose of allowing air to exit  
5 the housing.

When the cells in the cartridge are depleted, the entire cartridge can be easily removed, then replaced with a fresh cartridge. The cartridge and the housing are configured to interlock only when the cartridge is placed in the housing in the proper position. That is, the cartridge and housing interlock only when the  
10 air inlet opening in the cartridge and the air outlet opening of the housing align. In addition, the electrical contacts align in this position. This configuration prevents a consumer from placing the cartridge in the housing upside-down, or rotated by 180°.

All publications and patents mentioned in this application are herein  
15 incorporated by reference to the same extent as if each individual publication or patent was specifically and individually indicated to be incorporated by reference.

Other embodiments are within the scope of the following claims.

CLAIMS

1. An air manager system for a metal air cell comprising:
  - (a) a housing having an air mover and an air outlet opening;
  - (b) a cartridge that is removable from said housing, said cartridge
- 5 having first and second ends, first and second sides, and
  - (i) a metal air cell;
  - (ii) an air inlet opening located toward said first end of said cartridge and adjacent to said first side of said cartridge;
  - (iii) an air outlet opening located toward said second end of said
- 10 cartridge and adjacent to said second side of said cartridge;
  - (iv) a first diffusion tube communicating with said air inlet opening of said cartridge, said first diffusion tube extending along said first side of said cartridge;
  - (v) a second diffusion tube communicating with said air outlet
- 15 opening of said cartridge, said second diffusion tube extending along said second side of said cartridge;
  - (vi) a first distributor tube communicating with said first diffusion tube, said first distributor tube extending from said first diffusion tube along said first side of said cartridge through a change of direction and being
- 20 adjacent to an air plenum, said first distributor tube including a plurality of openings communicating with said air plenum; and
  - (vii) a second distributor tube communicating with said second diffusion tube, said second distributor tube extending from said second diffusion tube along said second side of said cartridge through a change of direction and
- 25 being adjacent to said air plenum, said second distributor tube including a plurality of openings communicating with said air plenum.
2. The air manager system of claim 1, wherein said cartridge further comprises:
  - (a) a first panel defining said openings of said first distributor tube,
- 30 wherein said first panel includes a ridge, and wherein said first panel and said ridge form two walls of said first diffusion tube and two walls of said first distributor tube; and

(b) a second panel defining said openings of said second distributor tube, wherein said second panel includes a ridge, and wherein said second panel and said ridge form two walls of said second diffusion tube and two walls of said second distributor tube.

5 3. The air manager system of claim 1, wherein said diffusion tubes, said distributor tubes, and said openings cooperate to define a plurality of air flow paths through said cartridge, all of said paths being substantially equal in length.

4. The air manager system of claim 1, wherein said air mover in said housing moves air into said air inlet opening of said cartridge.

10 5. The air manager system of claim 4, wherein said air mover is a blower.

6. The air manager system of claim 1, wherein said air mover in said housing extracts air from said air outlet opening of said cartridge.

7. The air manager system of claim 1, wherein said diffusion tubes are  
15 sized to permit an air flow rate therethrough of less than about  $3.46 \times 10^{-2}$  L/hour when said air mover is off.

8. The air manager system of claim 7, wherein said diffusion tubes are sized to permit an air flow rate therethrough of less than about  $3.46 \times 10^{-3}$  L/hour when said air mover is off.

20 9. The air manager system of claim 1, wherein each of said diffusion tubes has a cross-sectional area of about  $1 \text{ mm}^2$  to about  $8 \text{ mm}^2$  and a length of about 10 mm to about 70 mm.

10. The air manager system of claim 1, wherein said cartridge comprises a plurality of metal air cells.

25 11. The air manager system of claim 10, wherein said cells are positioned in stacks, and wherein each stack includes 2 cells that are spaced apart vertically to define an air flow path therebetween.

12. The air manager system of claim 11, wherein said cartridge comprises two stacks of cells, wherein said stacks are spaced apart horizontally.

30 13. The air manager system of claim 10, wherein said cells cooperate to define a battery that delivers a current of at least 300 mA when said air mover is on.

14. The air manager system of claim 13, wherein said cells cooperate to define a battery that delivers a current of at least 500 mA when said air mover is on.

15. The air manager system of claim 14, wherein said cells cooperate to  
5 define a battery that delivers a current of at least 1000 mA when said air mover is on.

16. The air manager system of claim 15, wherein said cells cooperate to define a battery that delivers an average current of about 1700 mA when said air mover is on.

10 17. The air manager system of claim 13, wherein said battery has an output current density of about 1 to 200 mA/cm<sup>2</sup> of air cathode surface when said air mover is on.

18. The air manager system of claim 17, wherein said battery has an output current density of about 10 to 110 mA/cm<sup>2</sup> of air cathode surface when said  
15 air mover is on.

19. The air manager system of claim 1, wherein said air mover generates an air flow rate through said cartridge of about 0.04 to 40 L/hour.

20. The air manager system of claim 19, wherein said air mover generates an air flow rate through said cartridge of about 4 to 40 L/hour.

20 21. The air manager system of claim 1, wherein said housing and said cartridge are configured such that when said cartridge is placed in said housing, said air outlet opening in said housing and said air inlet opening in said cartridge are substantially aligned.

22. The air manager system of claim 21, wherein said housing further  
25 comprises a cartridge release element that allows air to exit said housing.

23. The air manager system of claim 22, wherein said cartridge further comprises a locking tab that is configured to interlock with said cartridge release element.

24. An air manager system for a metal air cell comprising:  
30 (a) a housing having an air mover and an air outlet opening;  
(b) a cartridge that is removable from said housing, said cartridge having


- 11 -

- (i) a metal air cell;
  - (ii) an air inlet opening;
  - (iii) an air outlet opening;
  - (iv) a first diffusion tube in communication with said air inlet opening and a second diffusion tube in communication with said air outlet opening;
  - (v) a first distributor tube in communication with said first diffusion tube and a second distributor tube in communication with said second diffusion tube; and
  - (vi) a first panel defining a plurality of openings communicating with said first distributor tube and a second panel defining a plurality of openings communicating with said second distributor tube,
- wherein said diffusion tubes, said distributor tubes, and said openings cooperate to define a plurality of air flow paths from said air inlet opening of said cartridge, through said cartridge, to said air outlet opening of said cartridge, all of said paths being substantially equal in length.
25. A method for controlling air flow in a metal air battery comprising:
- (a) confining at least one metal air cell within a cartridge, said cartridge having an air inlet opening and an air outlet opening; and
  - (b) moving air through any of a plurality of air flow paths within said cartridge,
- wherein each of said paths passes through said air inlet opening of said cartridge, through a diffusion tube, through a distributor tube, across an active surface of a cell, and through said air outlet opening of said cartridge,
- and wherein all of said paths are substantially equal in length.
26. The method of claim 25, wherein each of said air flow paths passes through two diffusion tubes and two distributor tubes.
27. The method of claim 25, wherein each of said air flow paths passes through an opening in a panel.
28. The method of claim 25, wherein air is moved through said cartridge by an air mover exterior to said cartridge.
29. The method of claim 28, wherein said air mover pushes air into said cartridge.


30. The method of claim 29, wherein said air mover extracts air from said cartridge.
31. The method of claim 25, wherein step (b) includes moving air through a diffusion tube, changing the direction of air flow 180°, then moving air  
5 through a distributor tube.
32. The method of claim 31, wherein step (b) includes moving air through a diffusion tube, changing the direction of air flow 180°, moving air through a distributor tube, changing the direction of air flow 90°, then moving air across an active surface of a metal-air cell.

1/5


**FIG. 1**




**FIG. 2**






**FIG. 3**

**FIG. 4**



**FIG. 5**



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/25686

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H01M12/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 904 999 A (SHRIM YARON ET AL, JERUSALEM, ISRAEL) 18 May 1999 (1999-05-18) column 5, line 6 -column 7, line 43 figures 1,2,4	1-32
A	US 5 356 729 A (PEDICINI CHRISTOPHER S, MARIETTA, US) 18 October 1994 (1994-10-18) column 5, line 50 -column 6, line 54 figures 1-3	1-32

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

9 January 2001

Date of mailing of the international search report

16/01/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Peis, S

# INTERNATIONAL SEARCH REPORT

information on patent family members

Interr.      nal Application No

PCT/US 00/25686

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5904999	A	18-05-1999	US 5753384 A	19-05-1998
			US 6057052 A	02-05-2000
			EP 0744784 A	27-11-1996
			IL 116350 A	20-06-1999
US 5356729	A	18-10-1994	AU 7108394 A	03-01-1995
			CA 2163441 A	22-12-1994
			EP 0708992 A	01-05-1996
			JP 2753147 B	18-05-1998
			JP 8510085 T	22-10-1996
			WO 9429924 A	22-12-1994
			US 5560999 A	01-10-1996